

Clearview Stoves Pot Hanger and Chimney Net Fitting Instructions

It is important to minimise the risk of rain water leaking into the space between the chimney pot and liner. Clearview Stoves have for many years used a stainless steel pot hanger to ensure water does not seep into the chimney. In situations where the chimney pot and capping are in good condition and it is decided that the pot should not be removed a 'pot hanger' may be used to provide top support for the liner. A chimney net can be attached to the 'pot hanger' to prevent birds nesting and reduce the chance of rain entering the flue liner. The bird guard can be removed for easy inspection and cleaning without disrupting the 'pot hanger' seal. This simple arrangement provides a durable, long lasting seal at the top of the chimney and can allow the chimney void to be vented.

Step 1 – After insulating the liner place a top plate (and top fixing bracket) over the flexible flue liner and resting on the stack. The top plate can have vent holes to allow any steam to vent out of the chimney void. (Figure 1)

Step 2 - Place the pot on the top plate and over the flex (Figure 2). A mortar flaunching or capping (cast in situ) can now be applied to cap off the chimney. A vent pipe can be incorporated at this stage.



Figure 1



Figure 2

Step 3 – Fit the outer sleeve of the pot hanger over the flex that is protruding. Mark around the flexible flue where it extends out of the pot hanger sleeve (Figure 3). Then remove the sleeve and trim your flex down at this point. Back fill the void within your pot with insulation.



Figure 3

Step 4 - Refit the outer sleeve and then place the insert into the flexible flue and push down onto the sleeve. Fix the insert in place either with self tapping screws or some adhesive. Silicone adhesive can also be used under the outer edge of the sleeve where it sits on the pot.(Figure 4)



Figure 4



Figure 5

Step 5 - Place the chimney net (No.4) onto the pot hanger and attach both pot hanger and net into position using the jubilee clip provided. Try to fit this clip under the pot rim to prevent it from being able to slide off. (Figure 5)

The pot hanger and chimney net can now be inspected and removed separately, allowing for easy cleaning and inspection of the flue if necessary.

Items Required

Stainless Steel Pot Hanger – FF6PH, FF7PH	£56.00
Stainless Steel Chimney Net No. 4 (inc Jubilee Clip) – FS790	£74.00
Stainless Steel Top Plate – FF6P, FF7P	£27.00
Stainless Steel Top Bracket – FF6TB, FF7TB	£18.80

Or Buy a **Top Connection Kit** £170

Which includes - Pot Hanger, Chimney Net No. 4, top plate and bracket , 4 x self tapping screws (12mm)

Prices ex VAT.

Gloves must be worn when handling flexible flue and components

Clearview Stoves, More Works, Bishops Castle, Shropshire SY9 5HH